

LED Integrated Linkable Tube Series



T5 LED Integrated Linkable Tubes are a complete fitting replacement of traditional fluorescent fittings, typically used in cove and pelmet lighting. However they are also a great choice anywhere that needs a continuous beam. A minimalist fitting that can be used as an entire fitting - surface mounted or suspended.

Comes complete with easy mounting clips, screws, joiner piece and Australian plug, ready to install.



Product Features

- Join up to 8 units together for continuous light beam
- >85Lm/w efficacy, CRI >80%
- Aluminium Housing with PC Diffuser
- 5 Year Warranty



SPECIFICATION				
Size	270mm - 5w	570mm - 10w	870mm - 15w	1170mm - 20w
Model	T105-K05	T105-M10	T105-N15	T105-L20
Colour Temperature	3000k / 5000k	3000k / 5000k	3000k / 5000k	3000k / 5000k
Lumen (Lm)	435 / 480	890 / 980	1350 / 1485	1800 / 1980
Efficacy (Lm/w)	87 / 96	89 / 98	90 / 99	90 / 99
Light Source	SMD LED's			
Beam Angle	180°			
CRI	>80%			
Power Requirement	AC 100~240V			
Lifespan	> 40,000 hrs			
Operation Temp	-25°C~+40°C			
Warranty	5 Years			

Accessories:-

Flexible Joiner Cable:



3m Power Cable with Elbow Plug:

