

ENERGY SAVING LED TECHNOLOGY

LED ECONOMY WEATHERPROOF BATTEN SERIES



PRODUCT FEATURES

LED WEATHERPROOF BATTEN fittings are suitable for new installations or replacing existing fittings. They come complete with replaceable LED module and internal driver.

- CCT changeable 4000K, 5000K, 6000K
- Dual-power selectable
 - ▶ 600mm/2ft 10W/20W
 - ▶ 1200mm/4ft 20W/40W
- ABS base with PC lens
- Ø20mm conduit entry
- 110° Beam angle
- IP65 weatherproof
- IK08 impact resistant
- Optional
 - ► Maintained/non-maintained emergency backup
 - Microwave motion sensor with 3-step dimming
 - ► Remote control for microwave sensor settings (retains last setting)
 - Turtle Safe / Bug Free / Eyewash -Emergency





Product specifications



Economy Series

Weatherproof Battens

Available in a range of options and suitable for underground car parks, workshops, warehouses.

Optional: Motion sensor & Emergency battery back-up / Turtle Safe / Bug Free / Eyewash - Emergency for both 2FT and 4FT models

Specifications	*WP-ECOG3-2FT-CS			*WP-ECOG3-4FT-CS		
Colour temperature	4000K	5000K	6000K	4000K	5000K	6000K
Power selectable	10W / 20W			20W / 40W		
Lumen (lm) @ 10W (2FT) / 40W (4FT)	987lm	992lm	1,103lm	4,651lm	4,715lm	4,800lm
Efficiency	>101 ~ 110lm/w			>116 ~ 120lm/w		
Light source	SMD LEDs					
CRI	≥80 Ra					
Beam angle	110°					
Driver	Dual power					
Power requirement	AC 200 ~ 240V					
Operating temperature	-20°C ~ 60°C					
Lifespan	>50,000 hours					
Housing	ABS base with PC diffuser lens					
Dimensions (LxWxH)	600 x 95 x 80mm			1200 x 95 x 80mm		
Weight	0.82kg			1.28kg		
Protection rating	IP65 weatherproof IK08 impact resistant					
Warranty	3 Years					
Emergency backup	Add EM- prefix to product code (4FT only)					
Motion sensor	Microwave 3-step dimming with remote control programming Add -MS suffix to product code (4FT only)					

^{*} Optional: Turtle Safe / Bug Free / Eyewash ADD Suffix—"TLG" (i.e. WP-ECOG3-_FT-CS-TLG).

For Emergency, ADD Suffix "TLG-E" (i.e. WP-ECOG3-_FT-CS-TLG-E)

